

**THE LAST TWENTY YEARS EXPERIENCE WITH
FAST REACTORS : LESSONS LEARNT AND
PERSPECTIVE**

P.Chellapandi

S.C.Chetal

Prabat Kumar



Baldev Raj

**REACTOR ENGINEERING GROUP
INDIRA GANDHI CENTRE FOR ATOMIC RESEARCH
KALPAKKAM – 603 102, INDIA**

Role of FBR in India

- India is aiming to reach at least a per capita energy consumption of about 2400 kWh/a (current world average) with 8% growth rate by 2031-32.
- Electricity generation capacity of 778 GWe by 2031-32 (4 times in 20 y)
- Ten fold growth over next fifty years

- FBR with closed fuel cycle is essential for effective utilisation of available uranium
- To realise nuclear energy rapidly, breeding is important




FBR Programme in India

- India started FBR programme with the construction of FBTR
- FBTR is a 40 MWt (13.5 MWe) loop type reactor. The design is same as that of Rapsodie-Fortissimo except for incorporation of SG and TG (agreement signed with CEA, France in 1969).
- FBTR is in operation since 1985.
- 500 MWe Fast Breeder Reactor Project (PFBR) through Indigenous design and construction
- Govt. granted financial sanction for construction in Sep 2003.
- Construction of PFBR has been undertaken by BHAVINI.
- PFBR will be critical by 2011.
- Construction of 6 more reactors (2x500 MWe at Kalpakkam & 4x500 MWe at a new site) based on PFBR design in a phased manner (MOX fuel). Commercial operation of all six by 2020.
- Beyond 2020, metallic fuelled SFRs with 1000 MWe capacity

FBTR TODAY


FBTR, in operation since 1985, is the flag-ship of IGCAR and is the test bed for fast reactor fuels and materials. It has completed 15 irradiation campaigns with high availability factors in the recent campaigns. Its unique carbide fuel (55 % PUC & 45 % UC) has set an international record in burn-up by achieving 165 GWd/t without any single cladding failure in the core

- The performance of sodium systems has been excellent. Sodium pumps have crossed 6,00,000 h of cumulative, continuous operation. Steam generators have performed without a single leak incident
- PFBR test fuel is under irradiation and seen 92 GWd/t burn-up
- 44 % MOX fuel has been inducted in the core



FBTR life extension exercise has been completed to serve for another two decades, in particular for testing of advanced materials and metallic fuel


Experiences with FBTR




Post Irradiation Examination Facility for FBTR Fuel




Sodium Leak inside Purification Cabin due to a hole in valve body




25 GWd/t BURN-UP



50 GWd/t BURN-UP



100 GWd/t BURN-UP




155 GWd/t BURNUP

Experiences with FBTR – contd...



Fuel Handling Incident

During the transfer of the fuel subassembly from the 3rd ring to the storage location in 1987, the foot of the assembly got bent as it was projecting below the guide tube. This resulted in curtailed movement of the gripper tube and finally jamming of the fuel subassembly along with the gripper tube inside the guide tube.



- **Appropriate remedial measures, including mechanical stopper for fuel handling gripper and redundant interlocks for authorizing plug rotation, were implemented.**
- **Proper maintenance and operating procedures for the fuel handling mechanism were evolved.**
- **The remedial measures were so effective that the subsequent fuel-handling operations (about 600 nos.) have been carried out for the past 20 years without any incidents.**

APPROACH TO BIG LEAP IN FBR PROGRAMME



FBTR

40 MWt
13.5 MWe
Loop type
Fuel: PuC - UC

- 400 r-y worldwide FBR operational experience
- Rich experience with MOX fuel
- 30 y of focused R&D programme involving extensive testing and validation
- Material and Manufacturing Technology Development and Demonstration
- Science based technology
- Peer Reviews
- Synergism among DAE, R&D Institutions and Industries


PFBR

1250 MWt
500 MWe
Pool Type
Fuel: UO₂-PuO₂

key technology domains: Design Challenges, Mechanics & Hydraulics, Materials, Na, ISI & Fuel Cycle

FBR Challenges & Achievements

- Design for long reliable operation of components operating at high temperature (550°C) for design life of 40 years and more
- Design of mechanisms operating in sodium and argon cover gas space
- Design to accommodate Sodium leak and sodium water reactions
- Seismic design of interconnected buildings
- Seismic design of pumps, shutdown systems and thin shells with large sodium mass and fluid-structure interaction effects
- In-Service Inspection and repair of reactor internals
- High temperature fission chambers
- Manufacturing of large size thin walled vessels made of stainless steel with stringent form tolerances ($< \frac{1}{2}$ thickness)
- Erection of the vessels maintaining tight tolerances on verticality and horizontality.




Failure modes considered for the structural design

400 reactor years of worldwide operating experience is an asset to the design


Design to achieve economy with enhanced safety

Core Thermal Hydraulics


- ü Optimization of number of flow zones (more number results in complex administrative control for SA loading and lesser number calls for higher pump capacity)
- ü Temperature / flow distributions within a SA towards deriving accurate hot spot temperatures in fuel, clad and coolant. CFD analysis of 217 pin SA with thin wire wrap demands ~ 1 million mesh size




Thermal hydraulics analyses for confirmation of inter wrapper flow, adequacy of number and location of DNDs, carried out to confirm design adequacy for thermal striping criteria & core temp monitoring requirement



Precursor path from SA to detector location





Quantification of Inter-Wrapper Flow during Safety Grade Decay Heat Removal Conditions by CFD Studies




Finite Volume Mesh, Pressure and Temperature Distributions within 217 pin Fuel Subassembly

HIGH TEMPERATURE DESIGN: HIGHLIGHTS




Cyclic Hardening




Cyclic Softening


- Accurate prediction of stress / strain
- Appropriate constitutive equations to depict all complex mechanical material behaviour viz. rate and time dependent behaviour, monotonic & cyclic hardening/softening, plastic memorisation, etc.
- Materials: **SS 316 LN for Na components**
G91 steel for SG
- Chaboche Viscoplastic Theory:
 - ❖ 23-parameter model for SS 316 LN
 - ❖ 20-parameter model for G91 steel
- Identification of material parameters using experimental test data with physical meaning of each parameter.




ET test facility




IHX and SG tubes




ORNL Plate



Simulation of creep damage in IHX




Evolution of maxi. stress




Thermal ratcheting

Code development for viscoplastic analysis




Monotonic softening

- High strain rate sensitivity at ET
- Monotonic hardening at LT and softening at ET
- Cyclic softening (not strong function of temperature)
- Very low primary creep



Creep curves




Cyclic softening behaviour of G91


Numerical simulation of modified 9 Cr-1Mo

Experimental validation

- In-house code CONE with Chaboche model
- Critical Components: Control plug (CP), inner vessel (IV) and steam generator (SG)
- Elastic route of RCC-MR very conservative and hence not economical
- Viscoplastic model provides realistic stresses/ strains & higher operating temp./ longer life.




VM stress in SG-Header



VM stress in SG-Nozzle

Permissible Plant Life – Calendar Years

Analysis method	Operating Temp. °C		
	530	540	550
Elastic	51	17	10
Viscoplastic	132	82	63




VM stress in IV

Application: Life prediction of PFBR components


SEISMIC DESIGN

- Development of seismic design criteria
- Analysis of nuclear island connected buildings (NICB) and also extract floor response spectra at various component support locations
- Seismic analysis of reactor assembly to derive seismic forces
- Investigation of buckling of thin shells


- Ensuring the reactor scramability
- Investigation of pump seizure
- Shake table testing for validation of analysis and qualification
- R&D woks: Behaviour of bearing, non-linear sloshing, parametric instability of thin shells, study of cliff-edge effects, fluid-structure interaction of perforated structures





NICB model for seismic analysis



FEM model of RA



Buckling modes of thin vessels



Drop time of absorber rods




Shake table tests on RA model

Thickness H - mm	No of tests	Imperfection δ/h	Buckling load - t	
			Test	FEM
0.8	4	2.2 - 3.8	33-54	28-32
1.0	4	1.1 - 4.2	50-69	42-56
1.25	4	1.2 - 3.4	60-73	72-99




Experiment



Theory






Experiment





Theory

Loading	Tolerance mm	Test	FEM	Test/ FEM
Pressure P MPa	-2.7 to 1.7	0.9	0.95	0.95
Axial force F-t	-2.9 to 2.5	1.61	1.40	1.15
P plus F	-1.8 to 1.4	0.175 & 1.18	0.151 & 1.18	1.16


Safety Studies





Safety related to Sodium



Mechanical Consequences of Core Disruptive accident



Post Accident Heat Removal Studies






Cover gas hydrogen meter



Electrochemical in-sodium hydrogen meter




Polymer electrolyte based hydrogen sensor

**SENSORS FOR SODIUM APPLICATION
(DEVELOPED AT IGCAR)**



Electrochemical in-sodium carbon meter




Eddy Current Flow Meter



Semiconductor oxide based Compact hydrogen sensor

Risk Oxygen Meter




Special Features

Temp. range – up to 450°C

Resolution – from 13 ppb


Sensitivity –ppb to percentage

Response time – from 30 s



Sodium Ionisation Detector

Experimental Program for Qualification of RCC-MR




Crack growth tests in bends




SG -Shell-Nozzle Junction Tests



10 t Capacity Shake Table



Thermal ratcheting Primary pipe bends




High temperature tests

Pipe bends before insulation




Pipe bends after insulation


Technology Development of Reactor Assembly Components



PFBR – MANUFACTURING TECHNOLOGY DEVELOPMENT



Sector of Main Vessel



Sector of Inner Vessel




CSRDM



Sector of Roof Slab



Steam Generator



DSRDM



Butterfly Valve




IHX Tube to Tube Sheet
Joint Mock up



Large Dia Pipe
Fittings

PFBR – MANUFACTURING TECHNOLOGY DEVELOPMENT – contd..



Primary Pump Impeller Casting



Fuel Sub assembly



Primary pump - Shaft



Grid plate sector
Top plate rough machining



Bellow Development
Testing



Transfer Arm
Assembly in progress

Launching of Fast Breeder Power Reactor

- PFBR was launched on 23rd October, 2004 by Hon'ble Prime Minister Dr. Manmohan Singh during Golden Jubilee Year of DAE
- IGCAR to provide R&D; BHAVINI to bring project management expertise
- Both organizations to work in complete synergy with academic, research and industry




Unveiling of Foundation Stone for FBR Project




PFBR will be critical by Sept 2011

GRADE LEVEL OF NUCLEAR ISLAND, POWER ISLAND AND THE LEVEL OF SEA WATER DUE TO D.B.F. OF 1000 / 100 YEAR RETURN PERIOD AND TSUNAMI LEVEL OCCURRED ON 26th DEC. 2004.



Hard Facing of Grid Plate – contd...

Blue colored circles are the tracks



Preparatory work for hard facing




Hard Facing in Progress



Close up view of deposit and PTA torch

A 1 m diameter hard face track was deposited and tested at IGCAR under cyclic thermal loads simulating the reactor conditions to check and ensure the soundness of the hard face deposition. No cracks were noticed after the test.


Core Subassemblies



- Shielding assemblies (SS & B4C), Dummy fuel & blanket subassemblies delivered
- Precision machining and assembly requirements met

Achievements in Manufacturing of PFBR components

- Achieving high manufacturing tolerances for thin walled large diameter vessels better than those achieved internationally
- Precise machining tolerances for grid plate
- Indigenous development of hot facing technology with nickel base cobalt free material colomonoy
- Innovative methods of handling without practically no welded attachments on the vessel
- Consistency with the specified stringent erection tolerances




at




Grid plate with primary pipes



Inner vessel




Roof slab



Core support structure




Primary sodium pump




Steam generator

Successful Erection of Thin Shells



- Stringent erection tolerances
- Handling of thin shells without any permanent deformations
- No special welded joints for handling
- Challenging time schedule

Erection of safety vessel on reactor vault in June'08



Erection of main on reactor vault in Dec '09

Fuel Cycle for SFR


- Closed fuel cycle of PFBR through constructing a Fast Reactor Fuel Cycle Facility (FRFCF) at Kalpakkam.
- Co-location of the facility
- Basic technology is available
- The layout of FRFCF has been planned in such a way that expansion of the facility is possible to meet the requirements of two more 500 MWe FBRs



Fuel discharged from FBTR reprocessed in CORAL. Fuel with burn-up of 150 GWd/t has been successfully reprocessed

Next

Technology demonstration in DFR Plant
Commercial demonstration in PFBR fuel reprocessing plant



Strategy of Construction of Future FBRs

- Enhanced safety and improved economics are twin objectives.
- Means to achieve economy quantified: Increased design life to 60 yrs., design load factor of 85%, construction time 5 yrs., reduction in special steel specific weight requirement by ~ 20%, enhanced burn-up in a phased manner (Target: *Unit Energy Cost comparable to that of fossil power plants*)
- Mechanisms to achieve enhanced safety are being assessed: Elaborate in-service inspection and repair provisions, increased reliability of shut down systems and decay heat removal system, in-vessel purification system, innovative post accident heat removal provisions.
- Science based technologies and breakthroughs at interfaces in science & science with engineering to be harnessed for sustainable technological solutions
- Extensive involvement of Industries from developmental stages
- Giving due considerations to the innovative features conceived in the FRs under international projects (GEN IV and INPRO)

IGCAR

- Design
- R&D
- Safety Clearance
- Innovations

BHAVINI

- Construction
- Commissioning
- Operation

IGCAR & BHAVINI

- Planning for future FBRs
- Human Resources

Challenges, Approaches and Targets





Thank You

