


A large, stylized frame resembling a film strip, with black sprocket holes along its edges. It is centered on a blue sky background. Inside the frame, the title and author information are displayed in white text, and a photograph of the Borssele Nuclear Power Plant is visible at the bottom.

Ageing Management and Long Term Operation of NPP Borssele

André de Jong, NV EPZ

2nd Int. Symposium on NPP Life Management
15-18 October 2007 Shanghai, China

- Facts about NPP Borssele
- Current status of LTO: license
- Major upgrades
 - Safety upgrades from PSRs
 - Other important upgrades
- Ageing Management review in last PSR
- LTO activities



- 2-loop PWR designed and built by Siemens Kraftwerk Union (German company, now part of AREVA-NP)
- Construction started in 1969
- Commercial operation since 1973
- Gross capacity 515 MWe (1365 MWth): October/November 2006 upgrading 482 to 515 MWe by replacing turbine rotors and water separators
- Design operating life: 40 years (2013)
- 1 year cycle
- Mean load factor until now: 0.82, last years above 0,94
- Tendency towards shorter outages (< 2 weeks)



Current status of LTO: license aspects

- 1973: NPP Borssele in commercial operation: operating license without an end date
- 1994: political agreement closing NPP Borssele in 2003
- 1994-2006: lawsuits and political discussions about closing date of NPP Borssele, no end of license date (politics: 2013?, EPZ: why?)
- 16 June 2006: The Borssele Agreement:
 - ✓ NPP may operate until 2034 (60 years of operation)
 - ✓ NPP should be among the 25% safest Western water cooled NPPs
 - ✓ Immediate dismantling after closure
 - ✓ Shareholders will invest 250M€ in renewable energy projects
 - ✓ The government will invest another 250M€ in renewable energy projects
- From 30 to 40 to 60 years perspective in only a few years time!
- PSR regime: every ten years a Periodic Safety Review: no specific regulator policy on LTO



Safety upgrades: PSR overview

1. First 'PSR': Safety evaluation performed during 1982 – 1985 based on Post-TMI (Harrisburg) discussions

Backfitting Note Dutch Nuclear Regulatory Body (KFD):

→ PSR regulation (reviewing against state of the art)

2. 1989-1997: Modifications project: PSR + implementation of measures in 1997 (budget: 240M€)
3. 2000-2003: PSR, 2006,2007 implementing (minor) upgrades (25M€): hardware ok, only a few minor upgrades

EPZ Safety upgrades 1982-1985

Major:


Implementation of 2-train autonomous (10h) bunkered make-up and decay heat removal system

Other upgrade examples first 'PSR':

- Automatic test facility reactor protection system
- Modernization fire detection system
- Implementation accident and post-accident instrumentation
- Introduction of Westinghouse symptom based emergency procedures
- Installation active H₂-recombiner




Major safety upgrades implemented in 1997: New emergency diesels in a new separated building





Major safety upgrades implemented in 1997:

- Replacing the primary safety valves by Sebim tandem relief valves directly mounted on pressurizer dome (feed & bleed during severe situations)





Major safety upgrades implemented in 1997: A new control room





Other safety upgrades implemented in 1997:


- Additional bunkered building accommodating the reactor protection system
- New batteries with increased capacity
- Deep well system for long term cooling
- Seismic supports
- Leak before Break: new steam- and feedwater piping
- H₂-mitigation: passive cathodic recombiners
- Containment pressure relief system (filtered venting)
- Back-up control room and simulator



Major upgrades because of material degradation:

- Erosion-corrosion in steam-water systems in early years: several replacements and repair actions:
 - Heat exchangers
 - Valves
 - Some turbine blades
 - Piping


- In 1982 a big improvement was made by replacing the Cu-Ni condenser by a Ti condenser, the chemistry could be changed from phosphate chemistry to AVT chemistry: wastage of steam generator tubes stopped changed





Other upgrades because of material degradation

- Embrittlement of wires (spreader cabinet): in 1997 about 7700 wires were replaced: 'the red wire project'
- RPV-internals: replacement of several Inconel X-750 baffle-former bolts due to cracking (IGSCC)





Major upgrades in outage 2006

- Replacement of generator stator due to damage as a result of short circuits in the external grid
- New turbine rotors with higher efficiency and a new water separator:
→ 35 MWe Power Uprate





A changing view on Ageing Management (1995....)

- International awareness of the importance of good ageing management at NPPs
- IAEA guidelines on ageing management
- NPP Borssele: a new license after the 1997 back-fitting project with a requirement on ageing management demanded by the regulator
- Specific attention on ageing and ageing management in the PSR


☺ AM is not a new thing! The way how to do it is new.



Activities in AM after 1998

- AM studies:
 - report on ageing issues
 - interviews with experienced engineers
- implementation of ageing management team
- program for AM experience feedback
- development of AM database (experience feedback database)
- active involvement in several international projects/groups on AM (IAEA, VGB, OECD..)
- PSR (1993-2003) with special project on AM
- AMAT review 2003

EPZ AM experience feedback system



Specific project for review of AM:

- Screening for long living passive SSC (systems, structures or components) important to safety
- Ageing Management Review of long living passive SSC (RPV, primary piping, containment, SG's, buildings...)
- Comparing AM at KCB to latest IAEA guidelines and best practices

- Most SSC in good condition: operation until 2013 is no problem
- Some issues:
 - More study on irradiated assisted ageing for RPV internals
 - Some repair actions on important buildings (coating outside)
 - Some further repair on underground cooling water piping

- Objective to make an independent review of:
 - The ageing management system
 - The assessment of the ageing status of SSC important to safety (done for the PSR)
- Results:
 - according to AMAT team the SSC are, in general, in good condition and NPP Borssele has established a working Ageing Management System
 - recommendations and suggestions for further improvement of the existing ageing management
 - Identification of some good practices (e.g. the used AM database)



- Feasibility study on ageing management investments for 60 years
 - Safety and economics (PLIM)
 - Physical ageing and technological ageing (obsolescence)
 - All SSC involved
 - No detailed assessments: a general engineering view to determine financial consequences of LTO
 - Performed by AREVA in strong cooperation with EPZ-specialists



General results of study

- No replacements of major primary circuit components necessary since e.g.
 - ✓ Sufficient safety margins regarding RPV embrittlement
 - ✓ Appropriate SG tube behaviour without PWSCC
- Civil structures are well maintained and repair programs have been performed
- Some components need extra spares: e.g.
 - ✓ Heater rods pressurizer
 - ✓ CRDM's
- Some BOP heat exchangers need to be replaced
- Major replacements of I&C necessary due to obsolescence
- Scope of investments no threat for economical LTO!



Urgent LTO-activities on safety

- Update of Ageing Management Review
Reviewing potential ageing issues relating to 60 years of operation (next PSR and partly in progress)
- Update/renewal of Time Limited Ageing Analyses (TLAA's)



TLAA's: main topics

- RPV embrittlement, current TLAA comprises 40 years of operation
 - New surveillance program starting next outage
 - State of the art: both old (Charpy-V/ RT_{NDT}) and new concept (fracture toughness/Master Curve)
 - Two new sets of irradiated capsules + new set of unirradiated specimens
- Fatigue assessments of components important to safety, current TLAA's comprise 40 years
 - Implementing new monitoring systems to determine realistic P,T transients
 - New state of the art fatigue assessments
- Environmental Qualification of E&I components
 - Database with residual lifetime calculations of comp's
 - Implementing monitoring systems for monitoring environmental loads



Thank you for your attention!

Zeedijk 32, 4454 PM Borssele
PO Box 130, 4380 AC Vlissingen
The Netherlands
Telefoon 0031 113 – 356 000
E-mail: info@epz.nl
Website: www.epz.nl

The EPZ logo is centered in a white box. Below it, the words 'PURE' and 'POWER' are stacked in a bold, black, sans-serif font. The background of the entire slide is a silhouette of an industrial power plant at sunset, with a tall smokestack emitting a plume of dark smoke. The sky is a deep orange-red, and several high-voltage power lines are visible against the horizon.

EPZ
PURE
POWER

N.V. Elektriciteits-Produktiemaatschappij Zuid-Nederland EPZ