

Safe Storage of Zeolite Adsorbents used for Treatment of Accident-generated Water at Fukushima Daiichi Power Station


I. YAMAGISHI

Japan Atomic Energy Agency (JAEA)

R. Nagaishi, A. Terada, Y. Kamiji, C. Kato, K. Morita, K. Nishihara, Y. Tsubata (JAEA)
W. Ji, H. Fukushima, S. Sato (Hokkaido University)
Y. Okagaki (Utsunomiya University)
M. Denton (Kurion Inc.)

Safe storage of radioactive zeolites

Circulating Water Cooling at Fukushima-1 NPS




Hydrogen production from zeolite mixtures

Dose dependence of H₂ production^{*1}


^{*1} Kumagai *et al.*, *Transactions of the AESJ*, 10(4), 235 (2011).

Air-sat., R.T., dose rate 1-4 kGy/h



$$P [\text{mol/g}] = G [\text{mol/J}] \times D [\text{J/g}]$$


Formation of H₂ in aqueous phase and emission up to gas phase





- H₂ production: seawater(100 wt%) > seawater(50) + zeolite(50) > pure water(100). Because H₂ is oxidized to H₂O in pure water but not in seawater.
- Desalination & Dehydration are important for safe storage.

Thermal-hydraulic analysis

- Model, code: 3D full structure, FLUENT
- Zeolite: dried Herschelite loading Cs 0.07wt%





Schematic of KURION adsorption vessel & shield



Temperature

Less than 200 °C in zeolite bed





Hydrogen molar fraction

Hydrogen concentration less than 4% (under the lower explosive limit)

- The maximum temperature of zeolite bed (153°C) became **lower than the self-ignition temperature of hydrogen** (about 560°C).
- Opening end lines of water inlet/outlet and vent tubes, a kind of siphon effect occurred by buoyancy and difference of mixed gas density. **H₂ concentration in a vessel is kept lower than 4%**(the under explosive limit) .

⇒ **Opening of the tubes is effective for decreasing of H₂ concentration**


Corrosion of adsorption vessel with seawater




- Stress Corrosion Cracking (SCC) was not observed on the surface of U-bend coupons after the 1000-hour test (Cl⁻ 20,000 ppm) and 2000-hour tests (Cl⁻ 2,000 and 6,000 ppm) at 80 °C.

Estimation of Cs in zeolite by ZAC code


ZAC (Zeolite-Adsorption Column) code



Analysis of Cs in effluent



Column experiment



Estimation of Cs in zeolite

- Distribution of Cs in a vessel is a primary input for more precise evaluation.
- Improved code will be applied to the analysis of an actual vessel.

The results essential to the safe storage will be summarized by the end of FY 2013.